

E-LINE 82-7.5-2

The Gorman-Rupp E-Line 82-7.5-2 is an electric driven wet self-priming pump set for pumping clean and dirty water and for light or non-frequent use of abrasive fluids.

PRODUCT DESCRIPTION

Gorman-Rupp 82H52 self-priming centrifugal pump 7.5 kW IE3 premium efficiency electric motor with integrated variable frequency drive (VFD)

Control panel with mainswitch, emergency switch, pump on/off and speed control.

For detailed information, please refer to the QR code below.



SPECIFICATIONS

Suction size: 2"

Connection suction side: Perrot Male

Discharge size: 2"

Connection discharge side: Storz, camdistance 81 mm

Solids handling capacity: 19 mm

Dimensions: 1480 mm(L)*680 mm(W)*1090 mm(H)

Weight: 360 kg

Maximum flow: 47,5 m3/h

Maximum discharge head: 60 mWc





E-LINE 82-11-2

The Gorman-Rupp E-Line 82-11-2 is an electric driven wet self-priming pump set for pumping clean and dirty water and for light or non-frequent use of abrasive fluids.

PRODUCT DESCRIPTION

Gorman-Rupp 82H52 self-priming centrifugal pump

11 kW IE3 premium efficiency electric motor with integrated variable frequency drive (VFD)

Control panel with mainswitch, emergency switch, pump on/off and speed control.

For detailed information, please refer to the QR code below.



SPECIFICATIONS

Suction size: 2"

Connection suction side: Perrot Male

Discharge size: 2"

Connection discharge side: Storz, camdistance 81 mm

Solids handling capacity: 19 mm

Dimensions: 1480 mm(L)*680 mm(W)*1090 mm(H)

Weight: 440 kg

Maximum flow: 47,5 m3/h

Maximum discharge head: 63 mWc





E-LINE 83-11-2

The Gorman-Rupp E-Line 83-11-2 is an electric driven wet self-priming pump set for pumping clean and dirty water and for light or non-frequent use of abrasive fluids.

PRODUCT DESCRIPTION

Gorman-Rupp 83B52 self-priming centrifugal pump 11 kW IE3 premium efficiency electric motor with integrated variable frequency drive (VFD)

Control panel with mainswitch, emergency switch, pump on/off and speed control.

For detailed information, please refer to the QR code below.



SPECIFICATIONS

Suction size: 3"

Connection suction side: Perrot Male

Discharge size: 3"

Connection discharge side: Storz, camdistance 81 mm

Solids handling capacity: 20,6 mm

Dimensions: 1480 mm(L)*680 mm(W)*1090 mm(H)

Weight: 455 kg

Maximum flow: 90 m3/h

Maximum discharge head: 50 mWc





E-LINE 83-15-2

The Gorman-Rupp E-Line 83-15-2 is an electric driven wet self-priming pump set for pumping clean and dirty water and for light or non-frequent use of abrasive fluids.

PRODUCT DESCRIPTION

Gorman-Rupp 83B52 self-priming centrifugal pump 15 kW IE3 premium efficiency electric motor with integrated variable frequency drive (VFD)

Control panel with mainswitch, emergency switch, pump on/off and speed control.

For detailed information, please refer to the QR code below.



SPECIFICATIONS

Suction size: 3"

Connection suction side: Perrot Male

Discharge size: 3"

Connection discharge side: Storz, camdistance 81 mm

Solids handling capacity: 20,6 mm

Dimensions: 1480 mm(L)*680 mm(W)*1090 mm(H)

Weight: 470 kg

Maximum flow: 90 m3/h

Maximum discharge head: 54 mWc





E-LINE T2-5.5-4

The Gorman-Rupp E-Line T2-5.5-4 is an electric driven self-priming centrifugal pump set for pumping clean, dirty and sewage water.

PRODUCT DESCRIPTION

Gorman-Rupp T2C60SC self priming centrifugal pump

5,5 kW IE3 premium efficiency electric motor with integrated variable frequency drive (VFD)

Control panel with mainswitch, emergency switch, pump on/off and speed control.

For detailed information, please refer to the QR code below.



SPECIFICATIONS

Suction size: 2"

Connection suction side: Perrot Male

Discharge size: 2"

Connection discharge side: Perrot Male

Solids handling capacity: 38 mm

Dimensions: 1480 mm(L)*680 mm(W)*1090 mm(H)

Weight: 410 kg

Maximum flow: 47,5 m3/h

Maximum discharge head: 31,5 mWc





E-LINE T2-7.5-2

The Gorman-Rupp E-Line T2-7.5-2 is an electric driven self-priming centrifugal pump set for pumping clean, dirty and sewage water.

PRODUCT DESCRIPTION

Gorman-Rupp T2C60SC self priming centrifugal pump

7,5 kW IE3 premium efficiency electric motor with integrated variable frequency drive (VFD)

Control panel with mainswitch, emergency switch, pump on/off and speed control.

For detailed information, please refer to the QR code below.



SPECIFICATIONS

Suction size: 2"

Connection suction side: Perrot Male

Discharge size: 2"

Connection discharge side: Perrot Male

Solids handling capacity: 38 mm

Dimensions: 1480 mm(L)*680 mm(W)*1090 mm(H)

Weight: 415 kg

Maximum flow: 50 m3/h

Maximum discharge head: 34 mWc





E-LINE VPA3-5.5-4

The Gorman-Rupp E-Line VPA3-5.5-4 is an electric driven prime assisted centrifugal pump set for pumping clean, dirty and sewage water.

PRODUCT DESCRIPTION

Gorman-Rupp VPA3A60D prime assisted centrifugal pump 5,5 kW IE3 premium efficiency electric motor with integrated variable frequency drive (VFD)

Control panel with mainswitch, emergency switch, pump on/off and speed control.

For detailed information, please refer to the QR code below.



SPECIFICATIONS

Suction size: 3"

Connection suction side : Perrot Male

Discharge size: 3"

Connection discharge side : Perrot Male Solids handling capacity : 28,5 mm

Dimensions: 1680 mm(L)*680 mm(W)*1090 mm(H)

Weight: 415 kg

Maximum flow: 68 m3/h

Maximum discharge head: 22 mWc





E-LINE PAV4-22-6

The Gorman-Rupp E-Line PAV4-22-6 is an electric driven prime assisted centrifugal pump set for pumping clean and dirty water, sewage water and abrassive fluids.

PRODUCT DESCRIPTION

Gorman-Rupp 6404VA71 prime assisted vortex centrifugal pump 22 kW IE4 Super premium efficiency electric motor with variable frequency drive (VFD)

Control panel with mainswitch, emergency switch, pump on/off and speed control.

For detailed information, please refer to the QR code below.



SPECIFICATIONS

Suction size: 4"

Connection suction side: Perrot Male

Discharge size: 4"

Connection discharge side : Perrot Male

Solids handling capacity: 76,2 mm

Dimensions: 2295 mm(L)*1250 mm(W)*1660 mm(H)

Weight: 1480 kg

Maximum flow: 215 m3/h

Maximum discharge head: 25 mWc





E-LINE PAV4-30-4

The Gorman-Rupp E-Line PAV4-30-4 is an electric driven prime assisted centrifugal pump set for pumping clean and dirty water, sewage water and abrassive fluids.

PRODUCT DESCRIPTION

Gorman-Rupp 6404VA71 prime assisted vortex centrifugal pump 30 kW IE4 Super premium efficiency electric motor with variable frequency drive (VFD)

Control panel with mainswitch, emergency switch, pump on/off and speed control.

For detailed information, please refer to the QR code below.



SPECIFICATIONS

Suction size: 4"

Connection suction side: Perrot Male

Discharge size: 4"

Connection discharge side : Perrot Male

Solids handling capacity: 76,2 mm

Dimensions: 2295 mm(L)*1250 mm(W)*1660 mm(H)

Weight: 1515 kg

Maximum flow: 220 m3/h

Maximum discharge head: 30 mWc





E-LINE PAV6-22-6

The Gorman-Rupp E-Line PAV6-22-6 is an electric driven pime assisted centrifugal pump set for pumping clean- and dirty water, sewage water and abrassive fluids.

PRODUCT DESCRIPTION

Gorman-Rupp 6406VA71 prime assisted vortex centrifugal pump 22 kW IE4 Super premium efficiency electric motor with variable frequency drive (VFD)

Control panel with main switch, emergency switch, pump on/off and speed control.

For detailed information, please refer to the QR code below.



SPECIFICATIONS

Suction size: 6"

Connection suction side: Perrot Male

Discharge size: 6"

Connection discharge side : Perrot Male Solids handling capacity : 101,6 mm

Dimensions: 2425 mm(L)*1250 mm(W)*1660 mm(H)

Weight: 1650 kg

Maximum flow: 360 m3/h

Maximum discharge head: 22,5 mWc





E-LINE PA4-15-4

The Gorman-Rupp E-Line PA4-15-4 is an electric driven prime assisted centrifugal pump set for pumping clean, dirty and sewage water.

PRODUCT DESCRIPTION

Gorman-Rupp PA4A60D prime assisted centrifugal pump 15 kW IE4 Super premium efficiency electric motor with variable frequency drive (VFD)

Control panel with mainswitch, emergency switch, pump on/off and speed control.

For detailed information, please refer to the QR code below.



SPECIFICATIONS

Suction size: 4"

Connection suction side: Perrot Male

Discharge size: 4"

Connection discharge side : Perrot Male

Solids handling capacity: 76,2 mm

Dimensions: 2335 mm(L)*1250 mm(W)*1660 mm(H)

Weight: 1470 kg

Maximum flow: 160 m3/h

Maximum discharge head: 18 mWc





E-LINE PA4-30-4

The Gorman-Rupp E-Line PAV6-30-4 is an electric driven prime assisted centrifugal pump set for pumping clean and dirty water, sewage water and abrassive fluids.

PRODUCT DESCRIPTION

Gorman-Rupp PA4A60D prime assisted centrifugal pump 30 kW IE4 Super premium efficiency electric motor with variable frequency drive (VFD)

Control panel with mainswitch, emergency switch, pump on/off and speed control.

For detailed information, please refer to the QR code below.



SPECIFICATIONS

Suction size: 4"

Connection suction side: Perrot Male

Discharge size: 4"

Connection discharge side : Perrot Male Solids handling capacity : 76,2 mm

Dimensions: 2295 mm(L)*1250 mm(W)*1660 mm(H)

Weight: 1580 kg

Maximum flow: 205 m3/h

Maximum discharge head: 36,5 mWc





E-LINE PA6-30-4

The Gorman-Rupp E-Line PA6-30-4 is an electric driven pime assisted centrifugal pump set for pumping clean, dirty and sewage water.

PRODUCT DESCRIPTION

Gorman-Rupp PA6A60D prime assisted centrifugal pump 30 kW IE4 Super premium efficiency electric motor with variable frequency drive (VFD)

Control panel with mainswitch, emergency switch, pump on/off and speed control.

For detailed information, please refer to the QR code below.



SPECIFICATIONS

Suction size: 6"

Connection suction side: Perrot Male

Discharge size: 6"

Connection discharge side : Perrot Male

Solids handling capacity: 76,2 mm

Dimensions: 2415 mm(L)*1605 mm(W)*1660 mm(H)

Weight: 1865 kg

Maximum flow: 400 m3/h

Maximum discharge head: 38 mWc

